

	5' x 8' SA 5K	5' x 10' TA 7K
Model #	P5508LPDT	P7510LPDT
GVWR (lb.)	5000	7000
GAWR (lb. / Axle)	5200	3500
Curb Weight	1250	1780
Payload	3750	5220
Frame	4" Channel	5" Channel
Crossmembers	3" x 2" Angle	10 Gauge, Formed
Tongue	4" Channel	5" Channel
Coupler	Adjustable 2-5/16" Ball Coupler	
Jack	7K Bolt-On Drop Leg Jack	
Fenders	Diamond Plate	
Axles	5,000 lb. Greased	3,500 lb. Greased
Suspension	Double Eye Suspension	
Tires	225/75R15 LRD	205/75R15 LRC
Wheels	15", 6 on 5.5	15", 5 on 4.5
Volume Capacity	2.6 cu yd	3.2 cu yd
Lights	LED Lights - Rubber Mounted	
Electric Plug	7-Way SAE Plug	
Finish	PPG Industrial Polyurethane Paint	
Overall Length	147"	172"
Bed Width Inside	60"	
Bed Length Inside	96"	120"
Side Wall Height	20.5"	
Deck Height	26"	26"
Coupler Height	16" - 24"	14" - 22"
Gate	Double-Acting Tailgate w/ Chains	
Hydraulic Cylinder	One 3" x 24"	One 3.5" x 36"
Hydraulic Pump	12V Single Acting	
Battery	12V Deep-Cycle, DP24	
Dump Angle	48°	

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- 10-Gauge Floor
- 14-Gauge Sides (Single Axle)
- 12-Gauge Sides (Tandem Axle)
- Spare Tire Mount
- 2" x 4" Stake Pockets
- Sealed Wiring Harness
- Steel Lockable Pump Box
- Remote Control with 20' Cord
- Three Year Warranty

