

	6' x 12' 11K	7' x 12' 11K	7' x 14' 11K
<b>Model #</b>	P5CAM612FTT	P5CAM712FTT	P5CAM714FTT
<b>GVWR (lb.)</b>	11000	11000	11000
<b>GAWR (lb. / Axle)</b>	5200	5200	5200
<b>Curb Weight</b>	2300	2350	2560
<b>Payload</b>	8700	8650	8440
<b>Frame</b>	6"x4"x5/16" Angle		
<b>Crossmembers</b>	3" Channel		
<b>Tongue</b>	5" Channel @ 6.7lbs		
<b>Coupler</b>	Adjustable 2-5/16" Ball Coupler		
<b>Jack</b>	7K Bolt-On Drop Leg Jack		
<b>Fenders</b>	Diamond Plate		
<b>Axles</b>	5,200 lb. Greased		
<b>Suspension</b>	Slipper Spring Suspension		
<b>Tires</b>	225/75R15 LRD		
<b>Wheels</b>	15", 6 on 5.5		
<b>Decking</b>	Pressure-Treated Pine Decking		
<b>Lights</b>	LED Lights - Rubber Mounted		
<b>Electric Plug</b>	7-Way SAE Plug		
<b>Finish</b>	PPG Industrial Polyurethane Paint		
<b>Overall Length</b>	198"		222"
<b>Between Fenders</b>	75"		81"
<b>Deck Height</b>	16"		
<b>Coupler Height</b>	14" - 20.75"		
<b>Tilt Angle</b>	11°		10°

### ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System with Solar Charger
- Spare Tire Mount
- D-Ring Tie-Downs - 5/8" (4)
- Banjo Eye Tie-Downs (2)
- Sealed Wiring Harness
- Adjustable Hydraulic Cushion Cylinder
- Three Year Warranty

