

		15.4K	17.6K
Model #	18'	P7CAM18FTT	P8CAM18FTT
	20'	P7CAM20FTT	P8CAM20FTT
	22'	P7CAM22FTT	P8CAM22FTT
GVWR (lb.)		15400	17600
GAWR (lb. / Axle)		7000	8000
Curb Weight	18'	3280	3990
	20'	3500	4230
	22'	3720	4470
Payload	18'	12120	13610
	20'	11900	13370
	22'	11680	13130
Frame		6"x4"x3/8" Angle	6"x4"x1/2" Angle
Crossmembers		3" Channel	
Tongue		6" Channel @ 10.5 lbs.	
Coupler		Adjustable 2-5/16" Ball Coupler	
Jack		12K Bolt-On Drop Leg Jack	
Fenders		Diamond Plate	
Axles		7,000 lb. Greased	8,000 lb. Oil Bath
Suspension		Slipper Spring Suspension	
Tires		235/80R16 LRE	215/75R17.5 LRH
Wheels		16", 8 on 6.5	17.5", 8 on 6.5
Decking		Pressure-Treated Pine Decking	Oak Decking
Lights		LED Lights - Rubber Mounted	
Electric Plug		7-Way SAE Plug	
Finish		PPG Industrial Polyurethane Paint	
Length		268"	
Between Fenders		81"	
Deck Height		17"	22"
Coupler Height		14" - 18.5"	19" - 23.5"
Load Angle		9°	11°

## ADDITIONAL FEATURES

- SSafety Chains
- Zip Breakaway System with Solar Charger
- Diamond Plate Fenders
- 4" Drop Axles
- Spare Tire Mount
- D-Ring Tie Downs - 5/8" (6)
- Stake Pockets (8)
- Steel Toolbox
- Banjo Eye Tie-Downs (2)
- Sealed Wiring Harness
- Adjustable Hydraulic Cushion Cylinder
- Three Year Warranty

