



# EQUIPMENT TRAILERS

## FULL WIDTH

		11K	15.4K	17.6K
Model #	16+2	P5EC162CFW	P7EC162CFW	P8EC162CFW
	18+2	P5EC182CFW	P7EC182CFW	P8EC182CFW
	20+2	P5EC202CFW	P7EC202CFW	P8EC202CFW
	22+2	N/A	P7EC222CFW	P8EC222CFW
GVWR (lb.)		11000	15400	17600
GAWR (lb. / Axle)		5080	7000	8000
Curb Weight	16+2	2725	2960	3900
	18+2	2900	3160	4060
	20+2	3070	3350	4340
	22+2	N/A	3550	4620
Payload	16+2	8275	12440	13700
	18+2	8100	12240	13540
	20+2	7930	12050	13260
	22+2	N/A	11850	12980
Frame		5" Channel	6" Channel @ 8.2 lbs.	6" Channel @ 10.5 lbs.
Crossmembers		10 Gauge Fabricated	3" Channel	
Tongue		5" Channel @ 6.7lbs	6" Channel @ 8.2 lbs.	6" Channel @ 10.5 lbs.
Coupler		Adjustable 2-5/16" Ball Coupler		
Jack		7K Bolt-On Drop Leg Jack	12K Bolt-On Drop Leg Jack	
Fenders		Diamond Plate Drive Over Fenders		
Axles		5,200 lb. Greased	7,000 lb. Greased	8,000 lb. Oil Bath
Suspension		Slipper Spring Suspension		
Tires		225/75R15 LRD	235/80R16 LRE	215/75R17.5 LRH
Wheels		15", 6 on 5.5	16", 8 on 6.5	17.5", 8 on 6.5
Decking		Pressure-Treated Decking		Oak Decking
Lights		LED Lights - Rubber Mounted		
Electric Plug		7-Way SAE Plug		
Finish		PPG Industrial Polyurethane Paint		
Overall Length / Flat	16+2	268"		
	18+2	284"		
	20+2	308"		
	22+2	332"		
Deck Width		81"		
Deck Height		22.5"	25"	26"
Coupler Height		16.5" - 21"	17" - 21.5"	18" - 22.5"
Ramps		5' Steel Fabricated Ramps		5' Quick Release Angle Ramps

Additional configurations available. Refer to the dealer portal or contact your sales representative for more information.

## ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Spare Tire Mount
- D-Ring Tie-Downs (2)
- Stake Pockets (14)
- Rub Rail
- Steel Toolbox
- Banjo Eye Tie-Downs (2)
- Sealed Wiring Harness
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.