



DUMP TRAILERS

HEAVY DUTY SCISSOR HOIST

	82" x 12' 12K	82" x 14' 14K	82" x 16' 14K	82" x 14' 16K	82" x 16' 16K
Model #	PHDS8212-BP-120	PHDS8214-BP-140	PHDS8216-BP-140	PHDS8214-BP-160	PHDS8216-BP-160
GVWR (lb.)	12000	14000	14000	16000	16000
GAWR (lb. / Axle)	6000	7000	7000	8000	8000
Curb Weight	4100	4380	4660	4780	5060
Payload	7900	9620	9340	11220	10940
Frame	6" x 2" x 3/16" Rec. Tube			6" x 2" x 1/4" Rec. Tube	
Crossmembers	3" Structural Steel Channel				
Tongue	5" Channel				
Coupler	Adjustable 2-5/16" Ball Coupler				
Jack	12K Bolt-On Drop Leg Jack				
Fenders	Tread Plate				
Axles	6,000 lb. Greased	7,000 lb. Greased		8,000 lb. Oil Bath	
Suspension	Slipper Spring Suspension				
Tires	235/80R16 LRE			215/75R 17.5 LRH	
Wheels	16" 8 on 6.5"			17.5" 8 on 6.5"	
Decking	10 gauge, Smooth Steel				
Volume Capacity	6.07 cu yd	7.09 cu yd	8.10 cu yd	7.09 cu yd	8.10 cu yd
Lights	LED Lights - Rubber Mounted				
Electric Plug	7-Way SAE Plug				
Finish	PPG Industrial Polyurethane Paint				
Overall Length	198"	222"	246"	222"	246"
Bed Width Inside	82"				
Bed Length Inside	144"	168"	192"	168"	192"
Side Wall Height	24"				
Deck Height	29"				
Coupler Height	19" - 27"				
Gate	Triple-Acting Tailgate w/Chains				
Hydraulic Hoist	Scissor, Power-Up, Gravity-Down				
Hydraulic Pump	12V Single Acting				
Battery	12V Deep-Cycle, DP24		12V Deep-Cycle, Group 31		
Dump Angle	45°	43°	43°	43°	43°

ADDITIONAL FEATURES

- Safety Chains
- Zip Breakaway System
- Slide-Out Ladder Ramps (6')
- 10-Gauge Floor
- Spare Tire Mount
- D-Ring Tie-Downs - 1/2" (4)
- Stake Pockets and Rub Rail
- Integrated Tarp Shroud
- Mesh Tarp Installed
- Storage Tray
- Sealed Wiring Harness
- Steel Lockable Pump Box
- Remote Control with 20' Cord
- 110V Battery Charger
- Three Year Warranty



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.